

202 CERAMIC REPAIR HB ACTIVATOR

Page: 1 Compilation date: 20/04/2016

Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: 202 CERAMIC REPAIR HB ACTIVATOR

Product code: 202 HB

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name:	Resimac Limited
	Unit B, Park Barn Estate
	Station Road
	Topcliffe, Thirsk
	North Yorkshire
	YO7 3SE
	United Kingdom
Tel:	01845 577498
Email:	info@resimac.co.uk

1.4. Emergency telephone number

Emergency tel: 01845 577498

Section 2: Hazards identification

2.1. Classification of the substance or mixture		
Classification under CHIP: Xn: R20/21/22; C: R34; Sens.: R43; -: R52/53; Xn: R62		
Classification under CLP:	Acute Tox. 4: H302; Aquatic Chronic 3: H412; Repr. 2: H361f; Skin Corr. 1B: H314; Skin	
	Sens. 1: H317	
Most important adverse effects:	Harmful by inhalation, in contact with skin and if swallowed. Causes burns. May cause	
	sensitisation by skin contact. Harmful to aquatic organisms, may cause long-term	
	adverse effects in the aquatic environment. Possible risk of impaired fertility.	

2.2. Label elements

Label elements:				
Hazard statements:	H302: Harmful if swallowed.			
	H314: Causes severe skin burns and eye damage.			
	H317: May cause an allergic skin reaction.			
	H361f: Suspected of damaging fertility.			
	H412: Harmful to aquatic life with long lasting effects.			
Signal words:	Danger			

202 CERAMIC REPAIR HB ACTIVATOR

Page: 2

Hazard pictograms:	GHS05: Corrosion
	GHS07: Exclamation mark
	GHS08: Health hazard
Precautionary statements:	P102: Keep out of reach of children.
	P202: Do not handle until all safety precautions have been read and understood.
	P273: Avoid release to the environment.
	P260: Do not breathe vapours.
	P280: Wear protective gloves/protective clothing/eye protection/face protection.
	P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
	P302+352: IF ON SKIN: Wash with plenty of water/.
	P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
	P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove
	contact lenses, if present and easy to do. Continue rinsing.
	P333+313: If skin irritation or rash occurs: Get medical advice/attention.
	P501: Dispose of contents/container to hazardous or special waste collection point.
Label elements under CHIP:	
Hazard symbols:	Corrosive.
Risk phrases:	R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.
	R34: Causes burns.
	R43: May cause sensitisation by skin contact.
	R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the
	aquatic environment.
	R62: Possible risk of impaired fertility.
Safety phrases:	S1/2: Keep locked up and out of the reach of children.
	S26: In case of contact with eyes, rinse immediately with plenty of water and seek
	medical advice.
	S29: Do not empty into drains.
	S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.
	S45: In case of accident or if you feel unwell, seek medical advice immediately (show
	the label where possible).
2.3. Other hazards	

PBT: This product is not identified as a PBT/vPvB substance.

202 CERAMIC REPAIR HB ACTIVATOR

Page: 3

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

BENZYL ALCOHOL

EINECS CAS	CHIP Classification	CLP Classification	Percent
202-859-9 100-51-6 Xn: R20/22		Acute Tox. 4: H332; Acute Tox. 4: H302	10-30%

2,2'-IMINODIETHYLAMINE

203-865-4	111-40-0	Xn: R21/22; C: R34; Sens.: R43	Acute Tox. 4: H312; Acute Tox. 4: H302; Skin Corr. 1B: H314; Skin Sens. 1: H317	10-30%
-----------	----------	--------------------------------	---	--------

M-PHENYLENEBIS(METHYLAMINE)

216-032-5	1477-55-0	C: R34; Xn: R20/22; Sens.: R43	Skin Corr. 1B: H314; Acute Tox. 4:	10-30%
			H302; Skin Sens. 1: H317; Aquatic	
			Chronic 3: H412; Acute Tox. 4: H332	

3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE

220-666-8	2855-13-2	Xn: R21/22; C: R34; Sens.: R43; -:	Acute Tox. 4: H312; Acute Tox. 4: H302;	10-30%
		R52/53	Skin Corr. 1B: H314; Skin Sens. 1:	
			H317; Aquatic Chronic 3: H412	

4,4'-ISOPROPYLIDENEDIPHENOL

201-245-8	80-05-7	Xn: R62; Xi: R37; Xi: R41; Sens.:	Repr. 2: H361f; STOT SE 3: H335; Eye	1-10%
		R43; -: R52	Dam. 1: H318; Skin Sens. 1: H317	

SALICYLIC ACID

200-712-3	69-72-7	Xn: R22; Xi: R41	Eye Dam. 1: H318; Acute Tox. 4: H302+332	1-10%
REACTION PRODUCT FROM 1,3-BENZYLDIMETHANAMINE AND BISPHENOL A EPICHLOROHYDRIN				
-	113930-69-1	Xn: R22; Sens.: R43; N: R51/53	Aquatic Chronic 2: H411; Acute Tox. 4:	1-10%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact:	Remove all contaminated clothes and footwear immediately unless stuck to skin.
	Drench the affected skin with running water for 10 minutes or longer if substance is still
	on skin. Transfer to hospital if there are burns or symptoms of poisoning.
Eye contact:	Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist
	examination.
Ingestion:	Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10
	minutes. If unconscious, check for breathing and apply artificial respiration if necessary.
	If unconscious and breathing is OK, place in the recovery position. Transfer to hospital
	as soon as possible.

H302; Skin Sens. 1: H317

202 CERAMIC REPAIR HB ACTIVATOR

Page: 4

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

Ingestion: Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.

Inhalation: There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Corrosive. In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Notify the police and fire brigade immediately. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific

202 CERAMIC REPAIR HB ACTIVATOR

Page: 5

substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

2,2'-IMINODIETHYLAMINE

Workplace exposure limits:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	4.3 mg/m3	-	-	-

Respirable dust

4,4'-ISOPROPYLIDENEDIPHENOL

UK	5 mg/m3	5 mg/m3	-	-
----	---------	---------	---	---

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures:Ensure there is sufficient ventilation of the area.Respiratory protection:Self-contained breathing apparatus must be available in case of emergency.Hand protection:Impermeable gloves.Eye protection:Tightly fitting safety goggles. Ensure eye bath is to hand.Skin protection:Impermeable protective clothing.

Section 9: Physical and chemical properties

202 CERAMIC REPAIR HB ACTIVATOR

Page: 6 9.1. Information on basic physical and chemical properties State: Liquid Colour: Amber Odour: Ammoniacal Solubility in water: Insoluble Viscosity: Non-viscous Boiling point/range°C: >200 Flash point°C: >100 Autoflammability°C: 380 Relative density: 1.0 9.2. Other information Other information: No data available. Section 10: Stability and reactivity 10.1. Reactivity Reactivity: Stable under recommended transport or storage conditions. 10.2. Chemical stability Chemical stability: Stable under normal conditions. 10.3. Possibility of hazardous reactions Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions. Decomposition may occur on exposure to conditions or materials listed below. 10.4. Conditions to avoid Conditions to avoid: Heat. 10.5. Incompatible materials Materials to avoid: Strong oxidising agents. Strong acids. 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

BENZYL ALCOHOL

IVN	RAT	LD50	53	mg/kg
ORL	MUS	LD50	1360	mg/kg

202 CERAMIC REPAIR HB ACTIVATOR

				Page:
ORL	RAT	LD50	1230	mg/kg
2,2'-IMINODIETHYL	AMINE			
IPR	RAT	LD50	74	mg/kg
ORL	MUS	LD50	970	mg/kg
ORL	RAT	LD50	970	mg/kg
M-PHENYLENEBIS(
DERMAL	RAT	LD50	3100	mg/kg
ORAL	RAT	LD50	930	mg/kg
4,4'-ISOPROPYLIDE	NEDIPHENOL			
ORL	MUS	LD50	2400	mg/kg
ORL	RAT	LD50	3250	mg/kg

SALICYLIC ACID

DERMAL	RAT	LD50	>2000	mg/kg
ORAL	RAT	LD50	891	mg/kg

Relevant effects for mixture:

Effect	Route	Basis
Acute toxicity (harmful)	INH DRM ING	Hazardous: calculated
Corrosivity	OPT INH DRM	Hazardous: calculated
Sensitisation	DRM	Hazardous: calculated
Toxicity for reproduction		Hazardous: calculated

Symptoms / routes of exposure

Skin contact:	Blistering may occur. Progressive ulceration will occur if treatment is not immediate.
Eye contact:	Corneal burns may occur. May cause permanent damage.
Ingestion:	Corrosive burns may appear around the lips. Blood may be vomited. There may be
	bleeding from the mouth or nose.
Inhalation:	There may be shortness of breath with a burning sensation in the throat. Exposure may
	cause coughing or wheezing.
Delayed / immediate effects:	Immediate effects can be expected after short-term exposure.
Section 12: Ecological inform	ation

12.1. Toxicity

202 CERAMIC REPAIR HB ACTIVATOR

Page: 8

Hazardous ingredients:

M-PHENYLENEBIS(METHYLAMINE)

DAPHNIA	48H EC50	15.2	mg/l
FISH	96H LC50	>100	mg/l

SALICYLIC ACID

FISH 96H LC50 1380 mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

- company.
- **NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN2735

14.2. UN proper shipping name

Shipping name: AMINES, LIQUID, CORROSIVE, N.O.S.

(3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE)

14.3. Transport hazard class(es)

Transport class: 8

202 CERAMIC REPAIR HB ACTIVATOR

Marine pollutant: No

14.4. Packing group

Packing group: |||

14.5. Environmental hazards

Environmentally hazardous: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No
	453/2010.
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and s.3:	H302: Harmful if swallowed.
	H302+332: Harmful if swallowed or if inhaled.
	H312: Harmful in contact with skin.
	H314: Causes severe skin burns and eye damage.
	H317: May cause an allergic skin reaction.
	H318: Causes serious eye damage.
	H332: Harmful if inhaled.
	H335: May cause respiratory irritation.
	H361f: Suspected of damaging fertility.
	H411: Toxic to aquatic life with long lasting effects.
	H412: Harmful to aquatic life with long lasting effects.
	R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.
	R20/22: Harmful by inhalation and if swallowed.
	R21/22: Harmful in contact with skin and if swallowed.
	R22: Harmful if swallowed.
	R34: Causes burns.

202 CERAMIC REPAIR HB ACTIVATOR

R37: Irritating to respiratory system.R41: Risk of serious damage to eyes.R43: May cause sensitisation by skin contact.R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic
environment.R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the
aquatic environment.R52: Harmful to aquatic organisms, may cause long-term adverse effects in the
aquatic environment.R52: Harmful to aquatic organisms, may cause long-term adverse effects in the
aquatic environment.R52: Harmful to aquatic organisms.R62: Possible risk of impaired fertility.Legal disclaimer:The above information is believed to be correct but does not purport to be all inclusive
and shall be used only as a guide. This company shall not be held liable for any
damage resulting from handling or from contact with the above product.

Page: 10