

SAFETY DATA SHEET

RESICHEM 591 EPOXY SL ACTIVATOR

Page: 1 Compilation date: 27/05/2015

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: RESICHEM 591 EPOXY SL ACTIVATOR

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Resimac Limited

Unit B, Park Barn Estate Station Road Topcliffe, Thirsk North Yorkshire YO7 3SE United Kingdom Tel: +44 (0) 1845 577498 Email: info@resimac.co.uk

1.4. Emergency telephone number

Emergency tel: +44 (0) 1845 577498

Section 2: Hazards identification 2.1. Classification of the substance or mixture

Classification under CHIP: Xi: R36/38; Sens.: R43

Classification under CLP: Acute Tox. 4: H302; Aquatic Chronic 3: H412; Skin Corr. 1A: H314; Skin Sens. 1A: H317

Most important adverse effects: Irritating to eyes and skin. May cause sensitisation by skin contact.

2.2. Label elements

Label elements:	
Hazard statements:	H302: Harmful if swallowed.
	H314: Causes severe skin burns and eye damage.
	H317: May cause an allergic skin reaction.
	H412: Harmful to aquatic life with long lasting effects.
Signal words:	Danger
Hazard pictograms:	GHS05: Corrosion
	GHS07: Exclamation mark

		Page:	2
Precautionary statements:	P102: Keep out of reach of children.		
	P273: Avoid release to the environment.		
	P260: Do not breathe vapours.		
	P280: Wear protective gloves/protective clothing/eye protection/face protection.		
	P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.		
	P302+352: IF ON SKIN: Wash with plenty of water/.		
	P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.		
	P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove		
	contact lenses, if present and easy to do. Continue rinsing.		
	P333+313: If skin irritation or rash occurs: Get medical advice/attention.		
	P501: Dispose of contents/container to hazardous or special waste collection point.		
Label elements under CHIP:			
Hazard symbols:	Irritant.		



Risk phrases:	R36/38: Irritating to eyes and skin.
	R43: May cause sensitisation by skin contact.
Safety phrases:	S2: Keep out of the reach of children.
	S24: Avoid contact with skin.
	S37: Wear suitable gloves.
	S46: If swallowed, seek medical advice immediately and show this container or label.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

BENZYL ALCOHOL

EINECS	CAS	CHIP Classification	CLP Classification	Percent
202-859-9	100-51-6	Xn: R20/22	Acute Tox. 4: H332; Acute Tox. 4: H302 1	
4,4-METHYLEN	EBIS(CYCLOHE	XYLAMINE)		
217-168-8	1761-71-3	-	Skin Corr. 1A: H314; Aquatic Chronic	10-30%

		=,		
-168-8	1761-71-3	-	Skin Corr. 1A: H314; Aquatic Chronic	10-30%
			2: H411	

TRIMETHYLHEXANE-1,6-DIAMINE

247-063-2	25513-64-8	C: R34; Xn: R22; Sens.: R43	Skin Corr. 1C: H314; Acute Tox. 4: H302; Skin Sens. 1A: H317; Aquatic Chronic 3: H412; Acute Tox. 4: H312	1-10%
P-TOLUENE	SULPHONIC AC	D MONOHYDRATE		
203-180-0	6192-52-5	Xi: R36/37/38	Skin Irrit. 2: H315; Eye Irrit. 2: H319; STOT SE 3: H335	1-10%

Section 4: First aid measures

4.1. Description of first aid me	easures
Skin contact:	Remove all contaminated clothes and footwear immediately unless stuck to skin.
	Drench the affected skin with running water for 10 minutes or longer if substance is still
	on skin. Transfer to hospital if there are burns or symptoms of poisoning.
Eye contact:	Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist
	examination.
Ingestion:	Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10
	minutes. If unconscious, check for breathing and apply artificial respiration if necessary.
	If unconscious and breathing is OK, place in the recovery position. Transfer to hospital
	as soon as possible.
Inhalation:	Remove casualty from exposure ensuring one's own safety whilst doing so. If
	unconscious and breathing is OK, place in the recovery position. If conscious, ensure
	the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and
	provide oxygen if available. Transfer to hospital as soon as possible.
4.2. Most important symptom	s and effects, both acute and delayed
Skin contact:	Blistering may occur. Progressive ulceration will occur if treatment is not immediate.
Eye contact:	Corneal burns may occur. May cause permanent damage.
Ingestion:	Corrosive burns may appear around the lips. Blood may be vomited. There may be
	bleeding from the mouth or nose.
Inhalation:	There may be shortness of breath with a burning sensation in the throat. Exposure may
	cause coughing or wheezing.
Delayed / immediate effects:	Immediate effects can be expected after short-term exposure.
4.3. Indication of any immedia	te medical attention and special treatment needed
Immediate / special treatment:	Not applicable.
Section 5: Fire-fighting meas	ures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

Page: 5

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Corrosive. In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Notify the police and fire brigade immediately. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

Page: 6

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.
Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.
Hand protection: Impermeable gloves.
Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.
Skin protection: Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic phys	sical and chemical properties	
State:	Liquid	
Colour:	Yellow-brown	
Odour:	Ammoniacal	
Solubility in water:	Insoluble	
Viscosity:	Non-viscous	
Boiling point/range°C:	>200	Flash point°C: >100
Autoflammability°C:	380	Relative density: 1.0

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

BENZYL ALCOHOL

IVN	RAT	LD50	53	mg/kg
ORL	MUS	LD50	1360	mg/kg
ORL	RAT	LD50	1230	mg/kg

4,4-METHYLENEBIS(CYCLOHEXYLAMINE)

DERMAL	RBT	LD50	2110	mg/kg
ORAL	RAT	LD50	625	mg/kg

TRIMETHYLHEXANE-1,6-DIAMINE

DERMAL	RAT	LD50	1280	mg/kg
ORAL	RAT	LD50	910	mg/kg

P-TOLUENE SULPHONIC ACID MONOHYDRATE

ORAL RAT LD50 2480 mg/kg

Relevant effects for mixture:

Effect	Route	Basis
Irritation	OPT DRM	Hazardous: calculated
Sensitisation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

Ingestion: Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.

Inhalation: There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

174 mg/l

Hazardous ingredients:

4,4-METHYLENEBIS(CYCLOHEXYLAMINE)

Daphnia magna	48H EC50	6.84	mg/l	
---------------	----------	------	------	--

TRIMETHYLHEXANE-1,6-DIAMINE

FISH

48H EC50

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN2735

14.2. UN proper shipping name

Shipping name: AMINES, LIQUID, CORROSIVE, N.O.S.

(TRIMETHYLHEXANE-1,6-DIAMINE)

14.3. Transport hazard class(es)

Transport class: 8

14.4. Packing group

Packing group: ||

Page: 9

Marine pollutant: No

14.5. Environmental hazards

Environmentally hazardous: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No
	453/2010.
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and s.3:	H302: Harmful if swallowed.
	H312: Harmful in contact with skin.
	H314: Causes severe skin burns and eye damage.
	H315: Causes skin irritation.
	H317: May cause an allergic skin reaction.
	H319: Causes serious eye irritation.
	H332: Harmful if inhaled.
	H335: May cause respiratory irritation.
	H412: Harmful to aquatic life with long lasting effects.
	R20/22: Harmful by inhalation and if swallowed.
	R22: Harmful if swallowed.
	R34: Causes burns.
	R36/37/38: Irritating to eyes, respiratory system and skin.
	R36/38: Irritating to eyes and skin.
	R43: May cause sensitisation by skin contact.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive
	and shall be used only as a guide. This company shall not be held liable for any
	damage resulting from handling or from contact with the above product.